



FEATURES

- Universal 165 - 264VAC or 200 - 373VDC Input voltage
- Accepts AC or DC input (dual-use of same terminal)
- Operating ambient temperature range: -30°C ~ +70°C
- Low standby power consumption, high efficiency
- High I/O isolation test voltage up to 4000VAC
- Low ripple & noise
- Output short circuit, over-current, over-voltage protection
- Safety according to IEC/EN/UL62368, EN60335, GB4943
- Withstand 300VAC surge input for 5s
- Over-Voltage class III (designed to meet EN61558)
- Operating altitude up to 5000m

LM75-22Bxx series is one of Mornsun's enclosed AC-DC switching power supply. It features AC input and at the same time accepts DC input voltage, cost-effective, low no load power consumption, high efficiency and high reliability. These converters offer excellent EMC performance and meet IEC/EN61000-4, CISPR32/EN55032, IEC/UL/EN62368, EN60335, GB4943 standards and they are widely used in areas of industrial, LED, street light control, electricity, security, telecommunications, smart home etc.

Selection Guide

Certification	Part No.	Output Power(W)	Nominal Output Voltage and Current (Vo/Io)	Output Voltage Adjustable Range(V)	Efficiency at 230VAC (%) Typ.	Max. Capacitive Load (μF)
CE/CCC	LM75-22B05	70	5V/14A	4.5-5.5	86	10000
	LM75-22B12	72	12V/6A	10.2-13.8	88	6000
	LM75-22B15	75	15V/5A	13.5-18	88	5000
	LM75-22B24	76.8	24V/3.2A	21.6-28.8	90	1500
	LM75-22B48	76.8	48V/1.6A	43.2-52.8	91.5	680

Input Specifications





Item	Operating Conditions	Min.	Typ.	Max.	Unit
Input Voltage Range	AC input	165	--	264	VAC
	DC input	200	--	373	VDC
Input Voltage Frequency		47	--	63	Hz
Input Current	230VAC	--	--	1	A
Inrush Current	230VAC Cold start	--	65	--	
Hot Plug		Unavailable			

Output Specifications

Item	Operating Conditions	Min.	Typ.	Max.	Unit
Output Voltage Accuracy	Full load range	5V	--	±2	--
		12V/5V/4V/8V	--	±1	--
Line Regulation	Rated load	--	±0.5	--	%
Load Regulation	0% - 100% load	5V	--	±1	
		12V/5V/4V/8V	--	±0.5	--
Ripple & Noise*	20MHz bandwidth (peak-to-peak value)	5V	--	100	--
		12V/5V	--	120	--
		24V	--	150	--
		48V	--	200	--
Temperature Coefficient		--	±0.03	--	%/°C
Minimum Load		0	--	--	%
Stand-by Power Consumption		--	--	0.3	W

Hold-up Time	230VAC	20	--	--	ms
Short Circuit Protection	Recovery time <5s after the short circuit disappear.	Hiccup, continuous, self-recovery			
Over-current Protection		110%-150% Io, self-recovery			
Over-voltage Protection	5V	≤ 6.3VDC (Output voltage turn off, re-power on for recovery)			
	12V	≤ 16VDC (Output voltage clamp)			
	15V	≤ 22VDC (Output voltage clamp)			
	24V	≤ 35VDC (Output voltage clamp)			
	48V	≤ 60VDC (Output voltage turn off, re-power on for recovery)			
Note: *The "Tip and barrel method" is used for ripple and noise test, please refer to AC-DC Converter Application Notes for specific information.					

General Specifications

Item	Operating Conditions			Min.	Typ.	Max.	Unit	
Isolation Test	Input - 	Electric strength test for 1min., leakage current <10mA			2000	--	--	VAC
	Input-output				4000	--	--	
	Output - 				1250	--	--	
Insulation Resistance	Input - 	At 500VDC			100	--	--	MΩ
	Input - output				100	--	--	
	Output - 				100	--	--	
Operating Temperature				-30	--	+70	°C	
Storage Temperature				-40	--	+85		
Storage Humidity	Non-condensing			--	--	95	%RH	
Switching Frequency				--	65	--	kHz	
Power Derating	Operating temperature derating	5V output	+40°C ~ +70°C	1.3	--	--	% / °C	
		Other output	+50°C ~ +70°C	2	--	--		
Safety Standard				Meet IEC/EN/UL62368, EN60335, GB4943				
Safety Class				CLASS I				
MTBF	MIL-HDBK-217F@25°C			>300,000 h				



Mechanical Specifications

Case Material	Metal (AL1100, SGCC)
Dimensions	99.00 x 97.00 x 30.00 mm
Weight	210g (Typ.)
Cooling Method	Free air convection



Electromagnetic Compatibility (EMC)

Emissions	CE	CISPR32/EN55032 CLASS B		
	RE	CISPR32/EN55032 CLASS B		
	Harmonic current	IEC/EN61000-3-2 CLASS A		
Immunity	ESD	IEC/EN 61000-4-2	Contact ±6KV / Air ±8KV	Perf. Criteria A
	RS	IEC/EN 61000-4-3	10V/m	perf. Criteria A
	EFT	IEC/EN 61000-4-4	±2KV	perf. Criteria A
	Surge	IEC/EN 61000-4-5	line to line ±2KV/line to ground ±4KV	perf. Criteria A
	CS	IEC/EN61000-4-6	10 Vr.m.s	perf. Criteria A
	Voltage dips, short interruptions and voltage variations immunity	IEC/EN61000-4-11	0%, 70%	perf. Criteria B

Product Characteristic Curve



Note: ① This product is suitable for applications using natural air cooling; for applications in closed environment please consult Mornsun FAE.



Dimensions and Recommended Layout

THIRD ANGLE PROJECTION

Pin-Out	
Pin	Function
1	AC(L)
2	AC(N)
3	⏏
4	-Vo
5	+Vo

Note:
Unit: mm[inch]
Wire range: 22-12AWG
Tightening torque: M4 , 1.2N.m
General tolerances: ±1.00[±0.039]

Note:

1. For additional information on Product Packaging please refer to www.mornsun-power.com. Packaging bag number: 58220066;
2. Unless otherwise specified, parameters in this datasheet were measured under the conditions of $T_a=25^{\circ}\text{C}$, humidity<75%RH with nominal input voltage and rated output load;
3. The room temperature derating of $5^{\circ}\text{C}/1000\text{m}$ is needed for operating altitude greater than 2000m;
4. All index testing methods in this datasheet are based on our Company corporate standards;
5. In order to improve the efficiency at high input voltage, there will be audible noise generated, but it does not affect product performance and reliability;
6. We can provide product customization service, please contact our technicians directly for specific information;
7. Products are related to laws and regulations: see "Features" and "EMC";
8. Our products shall be classified according to ISO14001 and related environmental laws and regulations, and shall be handled by qualified units.

Mornsun Guangzhou Science & Technology Co., Ltd.

Address: No. 5, Kehui St. 1, Kehui Development Center, Science Ave., Guangzhou Science City, Huangpu District, Guangzhou, P. R. China

Tel: 86-20-38601850

Fax: 86-20-38601272

E-mail: info@mornsun.cn

www.mornsun-power.com