


40W isolation DC-DC converter with ultra-wide, ultra-high 200 - 1500VDC Specialize for H-Bridge driver circuit



RoHS 

FEATURES

- Ultra-wide 200 - 1500VDC input voltage range
- Industrial grade operating temperature: -40 °C to +75 °C
- High I/O isolation voltage up to 4000VAC
- High efficiency, high reliability, low ripple & noise
- Input under-voltage protection, input reverse polarity protection, output short circuit, over-current, over-voltage protection
- Operating altitude up to 5000m
- Surge immunity meets Level 3, EFT immunity meets Level 4
- Design refer to UL1741, EN/BS EN62109

PV40-29A、BxxH series is regulated DC-DC converters with an ultra-wide DC input of 200-1500VDC. The products feature high efficiency, high reliability, high insulation and high level of safety. It is mainly used in SVG, photovoltaic inverter, high-voltage inverter and other H-bridge power-taking occasions. The converters provide multiple protection features and guarantee stable and safe operating environments even under abnormal working conditions.

Selection Guide

Part No.	Output Power (W)	Nominal Output Voltage and Current*		Efficiency at 900VDC (%) Typ.	Capacitive Load (μF) Max.
		Vo1	Vo2		
PV40-29A15H	30	Vo1/Io1	15V/2A	86	2200
	10	Vo2/Io2	15V/0.67A		1000
PV40-29B15H	40	Vo/Io	15V/2.67A		2200

Note: *For PV40-29A15H, the non-isolated $\pm 15V$ output can be achieved through external connection of -Vo1 and +Vo2 pin.

Input Specifications

Item	Operating Conditions	Min.	Typ.	Max.	Unit
Input Voltage Range		200	--	1500	VDC
Input Current	300VDC	--	--	0.18	A
	1500VDC	--	--	0.04	
Inrush Current	1500VDC Cold start	--	--	100	
Input Under-voltage Protection	Under-voltage protection start	85	--	180	VDC
	Under-voltage protection release	120	--	200	
Input Reverse Polarity Protection		Available			
Start-up Delay Time		--	--	3	s
External Input Fuse Required		4A/1500VDC, required			
Hot Plug		Unavailable			

Output Specifications

Item	Operating Conditions	Min.	Typ.	Max.	Unit
Output Voltage Accuracy	All load range	--	± 2	--	
	Balanced load	PV40-29A15H	Vo1	± 2	
			Vo2	± 6	
Line Regulation	Rated load	--	± 1	--	%
Load Regulation	0% - 100% load	--	± 2	--	
	10% - 100% load	--	± 5	--	
Cross Regulation	10% - 100% load	--	--	10	
Stand-by Power Consumption	900VDC	--	--	1	W
Ripple & Noise*	20MHz bandwidth (peak-to-peak value)	--	--	200	mV
Temperature Coefficient		--	--	± 0.02	%/°C

Short Circuit Protection		Hiccup, continuous, self-recovery			
Over-current Protection		≥ 110%Io, hiccup, self-recovery			
Over-voltage Protection		≤ 18V	Output voltage clamp or hiccup		
Minimum Load	PV40-29B15H	0	--	--	%
	PV40-29A15H	10	--	--	

Note: *The "Tip and barrel method" and "parallel cable" method is used for ripple and noise test, please refer to PV Converter Application Notes for specific information.

General Specifications

Item	Operating Conditions		Min.	Typ.	Max.	Unit
Isolation	Input - output	Electric Strength Test for 1min., leakage current < 4mA	4000	--	--	VAC
Insulation Resistance	Input - output	Test voltage: 500VDC	50	--	--	MΩ
Operating Temperature			-40	--	+75	°C
Storage Temperature			-40	--	+85	
Storage Humidity	Non-condensing		--	--	95	%RH
Soldering Temperature	Wave-soldering		260 ± 5°C; time: 5 - 10s			
	Manual-soldering		360 ± 10°C; time: 3 - 5s			
Power Derating	-40°C to -10°C		1.33	--	--	%/°C
	+60°C to +75°C	200 - 1200V	4.00	--	--	
	+45°C to +60°C	1201-1500V	2.66	--	--	
	+60°C to +75°C		2.00	--	--	
	200 - 300VDC		0.30	--	--	%/VDC
	2000m - 5000m		6.67	--	--	%/Km
Switching Frequency			--	65	--	kHz
Safety Standard			Design refer to UL1741, EN/BS EN62109-1			
MTBF	MIL-HDBK-217F@25°C		≥ 300,000 h			



Mechanical Specifications



Case Material	Black plastic, flame-retardant and heat-resistant (UL94V-0)
Dimensions	89.00 x 63.50 x 25.00mm
Weight	190g (Typ.)
Cooling Method	Free air convection

Electromagnetic Compatibility (EMC)



Immunity	ESD	IEC/EN61000-4-2	Contact ±6KV/Air ±8KV	Perf. Criteria B
	RS	IEC/EN61000-4-3	10V/m	Perf. Criteria A
	EFT	IEC/EN61000-4-4	±4KV	Perf. Criteria B
	Surge	IEC/EN61000-4-5	Line to line ±1KV	Perf. Criteria B
	CS	IEC/EN61000-4-6	10Vr.m.s	Perf. Criteria A

Product Characteristic Curve





Note: 1. With a DC input between 200-300VDC, the output power must be derated as per temperature derating curves;
2. This product is suitable for applications using natural air cooling; for applications in closed environment please consult Mornsun FAE.



Design Reference

1. Typical application




Fig. 1

Component	Recommended value
FUSE	4A/1500VDC, required
C1	1 μ F/35V
C2	120 μ F/25V
TVS	SMBJ20A

Output Filter Components:



We recommend using an electrolytic capacitor with high frequency and low ESR rating for C2 (refer to manufacture's datasheet). Choose a capacitor voltage rating with at least 20% margin, in other words not exceeding 80%. C1 is a ceramic capacitor, used to filter high-frequency noise. TVS is a recommended suppressor diode to protect the application in case of a converter failure.

2. For additional information please refer to application notes on www.mornsun-power.com.


Dimensions and Recommended Layout

PV40-29A15H

THIRD ANGLE PROJECTION 



Note: Grid 2.54*2.54mm





Note:
Unit: mm[inch]
Pin diameter tolerances: ± 0.10 [± 0.004]
General tolerances: ± 0.50 [± 0.020]

Pin-Out	
Pin	Mark
1	-Vin
2	+Vin
3	+Vo2
4	-Vo2
5	No Pin
6	+Vo1
7	No Pin
8	-Vo1

PV40-29B15H

THIRD ANGLE PROJECTION 



Note: Grid 2.54*2.54mm

Pin-Out	
Pin	Mark
1	-Vin
2	+Vin
3	No Pin
4	No Pin
5	No Pin
6	+Vo1
7	No Pin
8	-Vo1

Note:
Unit: mm[inch]
Pin diameter tolerances: ± 0.10 [± 0.004]
General tolerances: ± 0.50 [± 0.020]

- Note:
1. For additional information on Product Packaging please refer to www.mornsun-power.com. Packaging bag number: 58220021;
 2. Unless otherwise specified, parameters in this datasheet were measured under the conditions of $T_a=25^\circ\text{C}$, humidity<75% with nominal input voltage and rated output load;
 3. All index testing methods in this datasheet are based on our company corporate standards;
 4. We can provide product customization service, please contact our technicians directly for specific information;
 5. Products are related to laws and regulations: see "Features" and "EMC";
 6. Our products shall be classified according to ISO14001 and related environmental laws and regulations, and shall be handled by qualified units.

Mornsun Guangzhou Science & Technology Co., Ltd.

Address: No. 5, Kehui St. 1, Kehui Development Center, Science Ave., Guangzhou Science City, Huangpu District, Guangzhou, P. R. China
Tel: 86-20-38601850 Fax: 86-20-38601272 E-mail: info@mornsun.cn www.mornsun-power.com